

# Pit Crew Tire Wedge Installation and Use

## GENERAL INFORMATION

The Pit Bull Pit Crew tire wedge(US patent pending) is an adjustable tire changing aid used with Pit Bull motorcycle stands. The Pit Crew provides temporary support for the front or rear tires during wheel removal and installation.



## INSTALLATION AND USE

### Wheel Removal:

1. Using the knurled height adjusting knob, lower the Pit Crew until it is fully retracted(Figure 1).
2. Using the Pit Bull Rear Stand or the Pit Bull front stand, place the Pit Bull Crew below the tire and snap onto the stand(Figure 2).
3. Use the knurled height adjusting knob to raise the Pit Crew until it makes contact with the bottom of the bike tire.
4. Remove the wheel according to manufacturer instructions.

### Wheel Installation:

1. Position the replacement wheel in the center of the Pit Crew and roll into place.
2. Install the wheel according to manufacturer's instructions. Adjust the height of the Pit Crew as needed to accommodate a new tire and remount the chain assembly.
3. Using the knurled height adjusting knob, lower the Pit Crew until it is fully retracted.
4. Unsnap the Pit Crew from the wheel stand.



Figure 1. Pit Crew



Figure 2. Pit Crew Mounted on Stand

**WARNING:** Keep fingers clear of Pit Crew when adjusting height.

**WARNING:** Do not raise or lower bike using your front or rear stand as the tire wedge could interfere and cause the bike to fall off the stand.

Pit Bull Products, Inc  
614 Pearl Ave NW  
Huntsville, AL 35801



Phone: 256-533-1977  
Fax: 256-533-3395  
Web: [www.pit-bull.com](http://www.pit-bull.com)  
Email: [info@pit-bull.com](mailto:info@pit-bull.com)